

2023

AVEN CATALOG

INSPECTION / PRECISION TOOLS







INSPECTION



MIGHTY SCOPES DIGITAL MICROSCOPES





USB Digital Microscope 5M Mighty Scope **V2** [10x-200x] on Metal Stand and advanced imaging software included

SKU **26700-218**



USB Digital Microscope 5M Mighty Scope **V2** [10x-200x] with Polarizer on Metal Stand and advanced imaging software included SKU **26700-218-PLR**



USB Digital Microscope 5M Mighty Scope **V2** [10x-200x] with Diffuser on Metal Stand and advanced imaging software included

SKU **26700-218-DFS**



USB Digital Microscope 5M Mighty Scope [500x] on Metal Stand and advanced imaging software included

SKU 26700-204

Optional Accesories



Diffuser Attachment for Mighty Scope V2 to reduce glare, hot spots, and provide soft & even illumination

SKU **26700-218-DIFF**

Flex Stand SKU **26700-212**



Dual View Stand SKU **26700-215**



3D Stand with LED SKU 26700-312-LED

ezlmageX3 Software

Features:

Image/video capture Measurement

Line, angle, and circle drawings/measurement Grid overlays

Compare modes and more

Built-in Features





MIGHTY SCOPE DIGITAL MICROSCOPES



	26700-218	26700-218-PLR	26700-218-DFS	26700-204
10x-200x optical and digital magnification		•	•	
Fixed magnification of 500x				
Working Distance At 10x (112mm), At 20x (42mm), At 30x (19mm), At 40x (8.5mm)	•	•	•	
Working Distance 0 to 3mm				
1/4" Color CMOS	•	•	•	
5M Effective Pixels	•	•	•	
USB 2.0 Signal Output		•	•	
Resolution based on a 24" monitor Max-190x 30 FPS 640 x 480, 1024 x 768, 1920x1080, 2048 x 1536 y 2592x1944	•	•	•	
Automatic Gain Control		•	•	
Snap Shot Mode Hardware & Software controls	•	•	•	•
Automatic White Balance	•	•	•	
5VDC through USB port Power Source	•	•	•	•
Windows 10-11, Mac OSX 10.11 or above		•	•	
Windows 10, Mac OSX 10.6 or above Note: macOS Catalina and above is not supported				•
8 Brightness controllable LEDs		•	•	
6 Brightness controllable LEDs				
Polarized		•		
Diffuser			•	
Metal Stand Included	•	•	•	



MIGHTY SCOPE CLEARVUE

DIGITAL MICROSCOPES





8x-25x Post Stand, 5" built-in HD screen and ezimagex3 Software included

SKU **26700-220-MNT**



8x-25x FlexArm Stand with Table Clamp, 5" built-in HD screen and ezimagex3 Software included

SKU 26700-220-557



8x-25x Post Stand and Gliding Stage, 5" built-in HD screen and ezimagex3 Software included

SKU **26700-220-479**



8x-25x with Adjustable Spring Balanced Arm and Weighted Base, 5" built-in HD screen and ezimagex3 Software included

SKU 26700-220-559WB



8x-25x FlexArm Stand with Magnetic Base, 5" built-in HD screen and ezimagex3 Software included



8x-25x with Adjustable Spring Balanced Arm with Table Clamp, 5" built-in HD screen and ezimagex3 Software included

SKU **26700-220-559**

Optional Accesories



Metal Post Stand SKU **26700-220-STN**



Compact Gliding Stage X/Y/R SKU **26800B-479**



Dual Gooseneck LED Task Light SKU **26537**



MIGHTY SCOPE CLEARVUE DIGITAL MICROSCOPES



	26700-220-MNT	26700-220-479	26700-220-558	26700-220-557	26700-220-559WB	26700-220-559
Image Sensor 1/4"M CMOS Sensor						
Effective Pixels 1920(H)X1080(V)						
Display 5" LCD Color TFT						
Interface Mini USB-Type A / HDMI						
2600mAh 18650 Li-ion Battery						
ezImageX3, measuring software Compatible with	•	•	•	•	•	•
USB cable	•	•	•	•	•	
Power supply	•	•	•	•	•	•
Snap shot remote control	•				•	•
32gb MicroSD Card	•	•	•	•	•	•
User guide	•	•	•	•	•	
Post Stand	•	•				
Flex Arm			•	•		
Balance Arm					•	•
Magnetic Base			•			
Table Clamp				•		•
Weighted Base					•	
Gliding Stage						



CYCLOPS DIGITAL MICROSCOPES





Cyclops HDMI [12x-132x] 2 Megapixel sensor, LED illumination with intensity control, large magnification range and long working distance. Infrared remote control included

SKU 26700-401





Lens 4X with Polarizer SKU 26700-400-PL01



4x Long Focus Lens SKU 26700-400-L-4XLF



Lens 10X SKU **26700-400-L10X**



Lens 4X SKU **26700-400-L4X**



Cyclops 3.0 [13x to 140x] 2 Megapixel sensor, built-in HDMI and 3.0 USB outputs, LED illumination with intensity control. Includes infrared remote control and advanced imaging and measurement software for PC mode

SKU **26700-423**



ADVANCED IMAGING SOFTWARE

- Make on-screen notes
- Utilize on-screen grids and overlays
- Capture stunning image and video files
- Calibrate Measurements
- Grid Overlays
- Line Drawing
- Angle Measurements
- Timelapse Photography



CYCLOPS DIGITAL MICROSCOPES



	26700-401	26700-423
HDMI port: Output 1080P(1920*1080 Pixel) image		•
USB 3.0 port: Type C Output YUV/MJPE format, Max Resolution: 1080p		
2 million pixels CMOS sensor		•
60 Frames Per Second		•
30 White LEDs with brightness & sector control		•
Remote Control for Lighting and Focus adjustment		•
Object lens 4X: 4/0.10,160/0.17		•
Magnification Object lens 4X: 13x~140x (based on a 24" monitor)		•
Focus IR remote control	•	•
Automatic Gain Control		
Manual and Automatic White Balance	•	•
Included 11 inch aluminum adjustable stand		
Power supplier: (Output: DC 5.0V/2.0A Input: AC 100-240V 50/60Hz)	•	•
0.225A(MAX) Power Consumption	•	•
Image/Video Capture Via Software		•
Advanced Imaging Software		•



Post Stand SKU **26700-400-STN**



Remote Control SKU 26700-400-RC



Power Supply SKU 26700-400-PWS







SPZ-50 STEREO ZOOM MICROSCOPES

magnification range



Binocular Microscope SPZ-50 10x Eyepieces on PLED Stand with Integrated LED Ring Light SKU 26800B-371



Binocular Microscope SPZ-50 10x Eyepieces on Post Stand with LED Ring Light and Adjustable Polarizer SKU 26800B-373-2



Binocular Microscope SPZ-50 10x Eyepieces on Post Stand with LED Ring Light and Polarizer

SKU 26800B-373-4



Binocular Microscope SPZ-50 10x Eyepieces on Post Stand with OLED Ring Light SKU **26800B-223-SPZ**



Binocular Microscope SPZ-50 10x Eyepieces on Articulating Arm Post Stand with Integrated LED Ring Light SKU **SPZ50-209-550-PCL**



Binocular Microscope SPZ-50 10x Eyepieces on Articulating Arm Post Stand with Arbor and Integrated LED Ring Light

SKU **SPZ50-01**



Binocular Microscope SPZ-50 10x Eyepieces on Articulating Arm Stand with Integrated LED Ring Light

SKU 26800B-373-5



Binocular Microscope SPZ-50 10x Eyepieces on Compact Articulating Arm Stand with Integrated LED Ring Light

SKU SPZ50-209-553



Binocular Microscope SPZ-50 10x Eyepieces on Compact Articulating Arm Stand with Arbor and Integrated LED Ring Light

SKU **SPZ50-02**



SPZ-50 STEREO ZOOM MICROSCOPES

magnification range 6.7x-50x



Binocular Microscope SPZ-50 10x Eyepieces on Double Arm Boom Stand with clamp and Integrated LED Ring Light SKU SPZ50-209-536



Binocular Microscope SPZ-50 10x Eyepieces on Double Arm Boom Stand and Integrated LED Ring Light

SKU 26800B-373-6



Binocular Microscope SPZ-50 10x Eyepieces on Double Arm Boom Stand with Arbor and Integrated LED Ring Light

SKU 26800B-369



Binocular Microscope SPZ-50 10x Eyepieces on Double Arm Boom Stand with OLED Ring Light

SKU SPZ-50-534-223



Binocular Microscope SPZV-50 10x Eyepieces on Track Stand with Top and Bottom LEDs

SKU **SPZ50-506**



Unibody Construction

Single lead screw assembly built on a single frame assures two lenses sit on a common axis. Prisms align correctly and always will.



Binocular Microscope SPZ-50 10x Eyepieces on Ultra Glide Boom Stand and Integrated LED Ring Light

SKU 26800B-373-1



Binocular Microscope SPZ-50 10x Eyepieces on Ultra Glide Boom Stand and LED FOI

SKU 26800B-373-8



Ideal Prism Installation

Dual prisms are made specifically for Aven-Carton brand scopes and fit snugly into each housing without springs



SPZ-50 STEREO ZOOM MICROSCOPE



Magnification
6.7x to 50x

Field of View
34.3 to 3.6 mm

Working Distance
108mm

Optical System
Greenough

SPZ-50 binocular stereo zoom microscopes offers the best in class zoom ratio with super sharp 3D images, wide field of view and long working distance which makes it an ideal choice for high throughput inspection stations and engineering and science labs. High precision optics ensures excellent contrast and high definition 3D images from edge to edge. Magnification range from 2.25x to 200x with optional auxiliary lenses and eyepieces. A wide variety of stands and illumination is available to provide you with a microscope system to meet your individual requirements.

Features

- Large zoom ratio 7.46:1 best zoom ratio in class
- Field of View 34.3mm to 3.6mm (1.35" to 0.14")
- Working distance 108mm(4.25") the best in class
- 17mm (0.67") high eye point wide field 10x eyepieces (field number 23) for comfortable viewing even for operators with eyeglasses
- Diopter adjustment on both eyepiece tubes

Body Type	Binocular, 360° rotatable, 45° inclined eyepiece tube
Eyepieces	Two 10x(FN23)eyepieces supplied with microscope body. Optional 15x(FN15) and 20x(FN11.4) available to extend magnification range
Auxiliary lens	0.5x, 0.75x, 1.6x and 2x auxiliary lenses available to extended magnification range of microscope
Working Distance	108mm without auxiliary lens 240mm with 0.5x auxiliary lens 132mm with 0.75x auxiliary lens 50mm with 1.6x auxiliary lens 41mm with 2x auxiliary lens
Zoom Ratio	17.46:1
Diopter Adjustment	On both eye tubes: +5.6D72D
Interpupillary Distance	Adjustable from 52 to 75mm
Optical System	Greenough




SPZ-50 STEREO ZOOM MICROSCOPES

Magnification | Work Distance | 45° inclined | 10x/FN23 | Diopter Adjustable | 6.7x-50x | 108mm | eyepiece tube | eyepieces | +5.6-0.72D

				Stan	d			LEC) Illur	ninati	on	(Came	ra
SPZ-50 BINOCULAR	PLED	Post	Track	Articulating	Double Arm	Ultra Glide	Arbor	Integrated	Polarizer	OLED	FOI	EIDOS	USB 3.0	Auto Focus
26800B-371	•							•						
26800B-373-2		•							A					
26800B-373-4		•							R					
26800-223-SPZ		•								•				
SPZ50-209-550-PCL				P				•						
SPZ50-01				P			•	•						
26800B-373-5				S										
SPZ50-209-553				M				•						
SPZ50-02				M			•	•						
SPZ50-209-536					C									
26800B-373-6					В			•						
26800B-369					В		•							
SPZ-50-534-223					В					•				
SPZ50-506			•											
26800B-373-1						•								
26800B-373-8						•					•			



SPZV-50 STEREO ZOOM MICROSCOPES





Trinocular Microscope SPZV-50 10x Eyepieces on Post Stand, EIDOS Camera with 11.6" built-in HD monitor and Integrated LED Ring Light

SKU **26800B-385**



Trinocular Microscope SPZV-50 10x Eyepieces on Post Stand, EIDOS Camera with 11.6" built-in HD monitor and Adjustable Polarizer

SKU 26800B-373-3



Trinocular Microscope SPZV-50 10x Eyepieces on Compact Articulating Arm Stand, EIDOS Camera with 11.6" built-in HD monitor and Integrated LED Ring Light

SKU SPZV50-03



Trinocular Microscope SPZV-50 10x Eyepieces on Post Stand with 3.0 USB 6M Camera and Integrated LED Ring Light

SKU 26800B-383



Trinocular Microscope SPZV-50 10x Eyepieces on Double Arm Boom Stand, EIDOS Camera with 11.6" built-in HD monitor and Integrated LED Ring Light

SKU SPZV50-04



Trinocular Microscope SPZV-50 10x Eyepieces on Ultra Glide Boom Stand with 3.0 USB 6M Camera and LED FOI

SKU 26800B-373-9



Single Screw Gear

By traveling on a single-screw mechanism, the objective lens stays aligned for the life of the microscope. Rust-resistant brass screws are used



Straight Light Path

Aven's dual prism design features a direct light path with one bend through its dual prisms. This prevents distortion from multiple light bends.



SPZV-50 STEREO ZOOM MICROSCOPES





Trinocular Microscope SPZV-50 10x Eyepieces on Ultra Glide Boom Stand with Mighty Cam Pro Auto Focus Camera and Integrated LED Ring Light

SKU SPZV50-05



Trinocular Microscope SPZV-50 10x Eyepieces on Double Arm Boom Stand with Mighty Cam Pro Auto Focus Camera and Integrated LED Ring Light

SKU SPZV50-07



Trinocular Microscope SPZV-50 10x Eyepieces on Articulating Arm Stand with Integrated LED Ring Light

SKU **SPZV50-209-550-PCL**



Trinocular Microscope SPZV-50 10x Eyepieces on Ultra Glide Boom Stand with Mighty Cam Pro Auto Focus Camera and FOI

SKU 26800B-373-10-PRO



Trinocular Microscope SPZV-50 10x Eyepieces on Post Stand with Mighty Cam Pro Auto Focus Camera and Integrated LED Ring Light

SKU **SPZV50-258-512**




Trinocular Microscope SPZV-50 10x Eyepieces on Track Stand with Top and Bottom LEDs

SKU SPZV50-506



Trinocular Microscope SPZV-50 10x Eyepieces on Ultra Glide Boom Stand with Arbor, Mighty Cam Pro Auto Focus Camera and Integrated LED Ring Light

SKU SPZV50-06



Greaseless Nylon Gears

Industrial-strength gears with tight tolerances operate smoothly with virtually no grease or oil.



SPZV-50 STEREO ZOOM MICROSCOPE



SPZV-50 true trinocular stereo zoom microscopes offers the best in class zoom ratio with super sharp 3D images, wide field of view and long working distance which makes it an ideal choice for inspection and capturing and viewing images on an monitor. High precision optics ensures excellent contrast and high definition 3D images from edge to edge. Magnification range from 3.35x to 200x with optional auxiliary lenses and eyepieces. A wide variety of stands, cameras and illumination is available to provide you with a microscope system to meet your individual requirements.

Features

- View images through the eyepiece or a monitor simultaneously
- Click stop zoom adjustment for accurate position
- Easy adjust C-mount camera adapter for fine focusing
- Large zoom ratio 7.46:1- best zoom ratio in class
- Field of View 34.3mm to 3.6mm (1.35" to 0.14")
- Working distance 108mm (4.25") -the best in class
- 17mm (0.67") high eye point wide field 10x eyepieces (field number 23) for comfortable viewing even for operators with eyeglasses
- Diopter adjustment on both eyepiece tubes

Magnification **6.7x to 50x**

Click stop zoom Adjustment

Working Distance
108mm

True Trinocular Greenough Microscope

Body Type	Trinocular, 360° rotatable, 45° inclined eyepiece tube
Eyepieces	Two 10x (FN23)eyepieces supplied with microscope body. Optional 15x(FN15) and 20x(FN11.4) available to extend magnification range
Auxiliary lens	0.5x, 0.75x, 1.6x and 2x auxiliary lenses available to extended magnification range of microscope
Working Distance	108mm without auxiliary lens 240mm with 0.5x auxiliary lens 132mm with 0.75x auxiliary lens 50mm with 1.6x auxiliary lens 41mm with 2x auxiliary lens
Zoom Ratio	7.46:1
Diopter Adjustment	On both eye tubes: +5.6D72D
Interpupillar y Distance	Adjustable from 52 to 75mm
Optical System	Greenough



SPZV-50 STEREO ZOOM MICROSCOPES

Magnification | Work Distance | 45° inclined | 10x/FN23 | Diopter Adjustable | eyepiece tube | eyepieces | +5.6-0.72D

				Stan	d			LE) Illur	minati	on	(Came	ra
SPZV-50 TRINOCULAR	PLED	Post	Track	Articulating	Double Arm	Ultra Glide	Arbor	Integrated	Polarizer	OLED	FO	EIDOS	USB 3.0	Auto Focus
26800B-385	•							•				•		
SPZV50-03				M				•				•		
SPZV50-04					В			•				•		
26800B-373-3		•							A			•		
26800B-383	•							•					•	
26800B-373-9						•					•		•	
SPZV50-05						•		•						•
26800B-373-10-PRO						•					F			•
SPZV50-06						•	•	•						•
SPZV50-07					В									•
SPZV50-258-512	•							•						•
SPZV50-209-550-PCL				P										
SPZV50-506			•											



SPZ-50 /SPZV-50 ESD

STEREO ZOOM MICROSCOPES





Binocular Microscope SPZ-50E 10x Eyepieces on PLED Stand with Integrated LED Ring Light SKU 26800B-371-ESD



Trinocular Microscope SPZV-50E 10x Eyepieces on PLED Stand with Integrated LED Ring Light SKU 26800B-376-ESD



Trinocular Microscope SPZV-50E 10x Eyepieces with 3.0 USB 6M Camera on Double Arm Boom Stand with Arbor and Integrated LED Ring Light

SKU **26800B-373-ESD**

ESD Safe coating protects sensitive components from electrostatic discharges





Trinocular Microscope SPZV-50E 10x Eyepieces on Post Stand with Mighty Cam Pro Auto Focus Camera and Integrated LED Ring Light SKU SPZV-50E-258-514-ESD



Trinocular Microscope SPZV-50E 10x Eyepieces on Post Stand, EIDOS Camera with 11.6" built-in HD monitor and Integrated LED Ring Light

SKU SPZV-50E-514-260



Trinocular Microscope SPZV-50E 10x Eyepieces on Post Stand with 3.0 USB 6M Camera and Integrated LED Ring Light

SKU 26800B-376-1



DSZ-44 / DSZV-44 STEREO ZOOM MICROSCOPES





Binocular Microscope DSZ-44 10x Eyepieces on Track Stand with Top and Bottom LEDs SKU **DSZ44-506**



Binocular Microscope DSZ-44 10x Eyepieces on Doble Arm Boom Stand with Integrated LED Ring Light

SKU **DSZ44-209-536**



Trinocular Microscope DSZV-44 10x Eyepieces on Post Stand, EIDOS Camera with 11.6" built-in HD monitor and Integrated LED Ring Light

SKU 26800B-339



Trinocular Microscope DSZV-44 10x Eyepieces on Track Stand with Top and Bottom LEDs SKU **DSZV44-506**



Binocular Microscope DSZ-44 10x Eyepieces on Double Arm Boom Stand with Integrated LED Ring Light

SKU **26800B-373-6**



Trinocular Microscope DSZV-44 10x Eyepieces on Post Stand with 3.0 USB 6M Camera and Integrated LED Ring Light

SKU 26800B-323



Binocular Microscope DSZ-44 10x Eyepieces on Compact Articulating Arm Stand with Integrated LED Ring Light



Binocular Microscope DSZ-44 10x Eyepieces on Ultra Glide Boom Stand with Integrated LED Ring Light

SKU 26800B-373-1



Trinocular Microscope DSZV-44 10x Eyepieces on Post Stand with Mighty Cam Pro Auto Focus and Integrated LED Ring Light

SKU **DSZV-44-258-512**



DSZ-44 STEREO ZOOM MICROSCOPES



Magnification

10x to 44x

Field of View **23mm to 5.2mm**

Working Distance **90mm**

Optical System **Greenough**

DSZ binocular stereo zoom microscopes offers superior quality optics and reliable mechanical components. This exceptional quality allows users to efficiently perform tasks and maintain high productivity. High precision optics ensures excellent contrast and definition 3D images from edge to edge. Magnification range from 2.5x to 140.8x with optional auxiliary lenses and eyepieces. A wide variety of lenses, stands and illumination is available to provide you with a microscope system to meet your individual requirements

Features

• Zoom ratio: 4.4:1

• Magnification range: 10x to 44x

• Field of view 23mm to 5.2mm

• Working distance: 90mm

• Wide Field 10x Eyepieces (Field Number 23)

Body Type	Binocular, 360° rotatable, 45° inclined eyepiece tube
Eyepieces	Two 10x (FN23) eyepieces supplied with microscope body. Optional 15x (FN15) and 20x (FN11.4) available to extend magnification range
Auxiliary lens	0.5x, 0.75x, 1.6x auxiliary lenses available to extended magnification range of microscope
Working Distance	 90mm without aux lens 150mm with 0.5x aux lens 105mm with 0.75x aux lens 45mm with 1.6x aux lens
Zoom Ratio	4.4:1
Diopter Adjustment	On both eye tubes: +5.6D - 0.72D
Interpupillary Distance	Adjustable from 52 to 75mm
Optical System	Greenough



DSZV-44 STEREO ZOOM MICROSCOPES



Magnification

10x to 44x

Field of View **23mm to 5.2mm**

Working Distance **90mm**

Optical System **Greenough**

DSZV dual view trinocular stereo zoom microscopes offers superior quality optics with the ability to view through both eyepieces and trinocular port simultaneously. This means you can view 3D images through your eyepieces and an external monitor connected to a camera on the trinocular port at the same time. Magnification range from 2.5x to 140.8x with optional auxiliary lenses and eyepieces. A wide variety of stands, cameras and illumination is available to provide you with a microscope system to meet your individual requirements.

Features

• Zoom ratio: 4.4:1

• Magnification range: 10x to 44x

• Field of view 23mm to 5.2mm

• Working distance: 90mm

• Wide Field 10x Eyepieces (Field Number 23)

D	T: 1 0/00 11 450
Body Type	Trinocular, 360° rotatable, 45° inclined eyepiece tube & C-mount camera port
Eyepieces	Two 10x (FN23) eyepieces supplied with microscope body. Optional 15x (FN15) and 20x (FN11.4) available to extend magnification range
Auxiliary lens	0.5x, 0.75x, 1.6x auxiliary lenses available to extended magnification range of microscope
Working Distance	 90mm without aux lens 150mm with 0.5x aux lens 105mm with 0.75x aux lens 45mm with 1.6x aux lens
Zoom Ratio	4.4:1
Diopter Adjustment	On both eye tubes: +5.6D - 0.72D
Interpupillary Distance	Adjustable from 52 to 75mm
Optical System	Greenough



DSZ-44 / DSZV-44 STEREO ZOOM MICROSCOPES



	Stand LED Illumination					Camera								
Magnification range 10x-44x	PLED	Post	Track	Articulating	Double Arm	Ultra Glide	Arbor	Integrated	Polarizer	OLED	FOI	EIDOS	USB 3.0	Auto Focus
DSZ44-506			•											
DSZV44-506			•											
				M				•						
DSZ44-209-536					С			•						
26800B-373-6					В			•						
26800B-373-1						•		•						
26800B-339	•							•				•		
26800B-323	•							•					•	
DSZV-44-258-512	•							•						•



SPZH-135 / SPZHT-135

STEREO ZOOM MICROSCOPES





Binocular Microscope SPZH-135 10x Eyepieces on Post Stand with Integrated LED Ring Light SKU 26800B-351



Binocular Microscope SPZH-135 10x Eyepieces on Track Stand with Top and Bottom LEDs SKU **SPZH135-506**



Trinocular Microscope SPZHT-135 10x Eyepieces on Track Stand with Top and Bottom LEDs

SKU **SPZHT135-506**



Trinocular Microscope SPZHT-135 10x Eyepieces on Double Arm Boom Stand with Integrated LED Ring Light

SKU SPZHT135-209-536



Binocular Microscope SPZH-135 10x Eyepieces on Ultra Glide Boom Stand with LED FOI

SKU **26800B-373-11**



Trinocular Microscope SPZHT-135 10x Eyepieces on Post Stand, EIDOS Camera with 11.6" built-in HD monitor and Integrated LED Ring Light

SKU **26800B-355**



Trinocular Microscope SPZHT-135 10x Eyepieces on Ultra Glide Boom Stand with USB 6M Camera and LED FOI

SKU 26800B-373-12



Trinocular Microscope SPZHT-135 10x Eyepieces on Post Stand with Mighty Cam Pro Auto Focus and Integrated LED Ring Light

SKU **SPZHT-135-258-512**



Trinocular Micrsocope SPZHT-135 10x Eyepieces on Ultra Glide Boom Stand with Mighty Cam Pro Auto Focus and FOI

SKU 26800B-373-13PRO



SPZH-135 STEREO ZOOM MICROSCOPES



Magnification
21x to 135x

15x eyepieces
at 45 degrees

Working Distance
84mm (3.3")

Optical System
Greenough

The ideal scope for a wide range of investigative, inspection applications, Aven's dynamic new microscope SPZH-135 extends the boundaries of stereo zoom microscopy, employing standard 15X eyepieces to achieve 21x to 135x continuous zoom magnification all the while providing a continuous working distance of 3.3" (84mm). Replacing the standard 15X eyepieces with our DHW20X eyepieces enhances the magnification range of this dynamic new microscope further – 28X to 180X. Having eyepieces set at a 45 degree angle, the adjustable interpupillary distance between eyepieces of 1.96" (50mm) to 2.91" (74mm) means they can be set to the comfort level of any user.

Features

- Total Magnification of 21X to 135X at 3.3" (84mm) working distance, Max 180X with 20X eyepieces
- Standard High Eye Point wide field 15x eyepieces at 45 degrees for comfortable viewing even for operators with eyeglasses
- Diopter adjustment on both eyepiece tubes
- Adjustable Interpupillary Distance of 1.96" (50mm) to 2.91" (74MM) accommodates any operator
- Multi coated optical components, free from chromatic and spherical aberration

Body Type	Binocular, 360° rotatable, 45° inclined eyepiece tube
Eyepieces	Two 15x (FN15) eyepieces supplied with microscope body. Optional 20x (FN11.4) available to extend magnification range
Magnification	21x to 135x, Max 180x with optional 20x eyepieces
Working Distance	84mm (3.3")
Interpupillary Distance	50mm (1.96") to 74mm (2.91")
Diopter Adjustment	+5.6D-7.2D on both eyepieces
Optical System	Greenough



SPZHT-135 STEREO ZOOM MICROSCOPES



The ideal scope for a wide range of investigative/inspection applications, Aven's dynamic new microscope SPZH-135 extends the boundaries of stereo zoom microscopy, employing standard 15X eyepieces to achieve 21x to 135x continuous zoom magnification all the while providing a continuous working distance of 3.3" (84mm). Replacing the standard 15X eyepieces with our DHW20X eyepieces enhances the magnification range of this dynamic new microscope further – 28X to 180X. Having eyepieces set at a 45 degree angle, the adjustable interpupillary distance between eyepieces of 1.96" (50mm) to 2.91" (74mm) means they can be set to the comfort level of any user.

Features

- Total Magnification of 21X to 135X at 3.3" (84mm) working distance, Max 180X with 20X eyepieces
- Click stop zoom adjustments for accurate, repeatable measurement
- Standard High Eye Point wide field 15x eyepieces at 45 degrees for comfortable viewing even for operators with eyeglasses
- Diopter adjustment on both eyepiece tubes
- Adjustable Interpupillary Distance of 1.96" (50mm) to 2.91" (74MM) accommodates any operator
- Multi coated optical components, free from chromatic and spherical aberration
- One touch fine focus adjust trinocular camera port for quick, easy camera focusing and parfocaling the scope

Magnification
21x to 135x

15x eyepieces
at 45 degrees

Working Distance
84mm (3.3")

Optical System
Greenough

Dl T	
r	Trinocular, 360° rotatable, 45° inclined eyepiece tube
6 r (Two 15x (FN15) eyepieces supplied with microscope body. Optional 20x (FN11.4) available to extend magnification range
\	21x to 135x, Max 180x with optional 20x eyepieces
Working { Distance	84mm (3.3")
Zoom Ratio	4:4:1
	50mm (1.96") to 74mm (2.91")
0.0000	+5.6D-7.2D on both eyepieces
Optical System (Greenough



SPZH-135 / SPZHT-135 STEREO ZOOM MICROSCOPES

BINOCULAR-TRINOCULAR

	Stand					LED Illumination				Camera				
Magnification range 21x-135x	PLED	Post	Track	Articulating	Double Arm	Ultra Glide	Arbor	Integrated	Polarizer	OLED	FO.	EIDOS	USB 3.0	Auto Focus
26800B-351	•							•						
SPZH135-506			•											
SPZHT135-506			•											
SPZHT135-209-536					С									
26800B-373-11						•					•			
26800B-355	•											•		
26800B-373-12						•					•		•	
SPZHT-135-258-512	•							•						•
26800B-373-13PRO						•					•			•



PLED



Pole Stand with Focus Mount and LED Illumination

SKU 26800B-512

- Rack & pinion focus mount with course and fine adjustment knobs
- · Built in 60 LED ring light with dimmer control
- · Base Size: 220mm x 284mm Vertical Post 250mm

POST



Pole Stand with Focus Mount

SKU 26800B-511

- · Comes with rack & pinion focus mount with course adjustment knobs
- · Base Size: 220mm x 284mm
- · Vertical Post: 250mm

RACK



Track Stand with Top and Bottom LED Lights

SKU 26800B-506

- · Individual dimmer controls
- · Built-in clips for securing slides
- Frosted glass diffusion plate
- \cdot Coarse and fine focus adjustment
- · Base Size: 284.7mm x 237.7mm Focusing Distance: 106mm

Double Arm Boom Stand with Table Clamp

SKU **26800B-536**

- Smooth movement of a ball bearing slide
- · Horizontal Arm: 570mm
- · Vertical Post: 384mm
- · Clamp Opening: 0-40mm

JOUBLE ARMS



Double Arm Boom Stand w/Heavy Metal Base

SKU **26800B-534**

- · Smooth movement of a ball bearing slide
- Base Size: 285mm x 260mm
- · Horizontal Arm: 384mm
- · Vertical Post: 380mm

STANDS & ACCESORIES



Standard Articulating Arm Stand

SKU 26800B-560

- · Vertical and horizontal adjustment
- Revolution 360° in horizontal direction
- · Arm Length: 500mm Clamp Opening:60mm

ARTICULATING ARMS

Articulating Arm Stand with Vertical Post and Table Clamp

SKU **26800B-550-PCL**

- ·Vertical and horizontal adjustment
- Revolution 360° in horizontal direction
- · Arm Length: 800mm
- · Vertical post: 384mm
- · Clamp Opening:60mm



Articulating Arm Post Stand with Microscope Mount and Table Clamp

SKU 26800B-553

- · Compact and convenient
- · Arm Length: 414.8mm
- · Vertical post: 449.6mm
- · Clamp Opening:99.8mm

LTRA GLIDE



Ultra-Glide Arm Stand w/Heavy Metal Base

SKU 26800B-556

- ·Gliding boom provides smooth horizontal movement
- · Base Size: 381mm x 266.7mm
- · Vertical Post: 342.9mm
- · Horizontal Arm: 584.2mm

ARROR



Tiltable Arbor

SKU 26800B-521

- · Extends working range
- · Tiltable
- · Vertical post: 245mm



LED ILLUMINATION

INTEGRATED



E-Arm Focus Mount w/Integrated LED Ring Light and Brightness Controller

SKU 26200B-209

- · Focus mount: 74mm diameter with coarse focus
- \cdot 60 integrated LED ring light with dimmer control
- · Has 5/8" adapter for mounting
- · Light Intensity: 35,000 lux
- · LED Color Temperature: 5600K White

LED Ring Light w/Brightness and Sector Control

SKU 26200B-211

Focus Mount w/Integrated LED Ring Light and

· Focus mount: 74mm diameter with coarse and fine focus

· 60 integrated LED ring light with dimmer control

- LED Ring Light w/Brightness and Sector Control
- · 60 High Intensity LED Lights
- · 7 Step Intensity Control and 4 Independent Zones
- · ColorTemperature 5500K White
- · Light Intensity 35,000 lux
- · Inner Diameter 62mm



OLED Ring Light for Microscopes

SKU 26200B-223

- · Organic Light Emitting Diode
- · Dimmer Control Box
- Ring light with 4 OLED panels
- · Each panel can be tilted up and
- · Illuminance at 100mm: MIN 800lx ~ MAX 2,500lx (5,000lx w/tilted panels)
- · Color Temperature: 5400K



Brightness Controller

· Mounting Diameter: 26.9mm

· LED Color Temperature: 5600K White

· Light Intensity: 35,000 lux

SKU 26200B-207



LED Ring Light with Adjustable Polarizer

SKU 26200B-222

- . 120 adjustable, ultra-bright SMD LEDs
- Polarizer dial with reference markers to adjust the level of polarization
- Includes a tinted glass analyzer insert for enhanced polarization effects

POLARIZER



Ring Light LED with Polarize

SKU 26200B-214

Polarizer with Analyzer reduces glare and reflections from shiny parts

No color change with temperature Energy saving and eco friendly



Fiber Optic Illuminator 24W

SKU **26200A-310**

- · The light source is an ultra-bright and energy efficient LED
- Adjustable brightness intensity up
- · Anti-static metal construction Color Temperature: 5600K Illumination Intensity:1600Lx



CAMERAS

AUTO FOCUS

AVEN 20100-238



Mighty Cam Pro Auto Focus Camera with USB+HDMI Outputs and SD Card Port

SKU **26100-258**

- · 1080p Full HD Imaging at 60 FPS
- \cdot USB output connects to PC
- · Sensor CMOS
- · Dynamic Resolution 2MP, 1920x1080
- · Static Resolution 6MP, 3264x1836
- · Frame Rate 60fps @HDMI, 30fps @USB2.0
- · Built-in measurement software No PC required
- \cdot Advanced measurement software included for computer connectivity
- · Real-time image stitching
- · Depth of field detection
- · Achieve instant auto focus
- · Save high resolution image/video files directly to SD card

JSB 3.0





Mighty Cam USB 3.0 6MP CMOS Camera with Imaging Software

SKU 26100-244

- \cdot Professional Sony 6M CMOS Sensor (3072(H) \times 2048(V))
- · Easy Plug and Play USB 3.0 Interface
- · Resolution: 3072(H) x 2048(V)
- · Frame Rate: 40fps @6MP
- · Operating System: Windows/Mac
- · Save high resolution image files
- · Create large panoramic images with real-time stitching feature
- · Calibrate accurate measurements
- · Real-Time Depth of Field Adjustment









Mighty Cam Eidos - 5M Camera with Integrated 11.6" HD Monitor

SKU **26100-260**

- · All-in-one, compact system
- · 11.6" built-in HD LCD monitor
- · 1080p Full HD Imaging at 60 FPS
- · Effective Pixels 5M
- · Resolution 1920*1080P@60FPS
- · HDMI Output for additional monitor viewing
- · 1080p Full HD Output
- · Built-in measurement software No PC required

- \cdot Save high resolution image/video files directly to USB Storage card
- Monitor can be tilted to the optimal viewing angle
 Basic Function: Image Capture, Video, Measurement
- · Image Adjustment: Exposure, Color Temperature, White Balance
- · Camera Function: Mirror, Freeze, Flip. Wide Dynamic, Zoom In, Zoom Out
- · Grid: Vertical/Horizontal Lines, Color/Size can be adjusted



MACRO-MICRO ZOOM VIDEO INSPECTION SYSTEMS

All-in-one camera monitor · Autofocus camera · USB digital camera



Macro Zoom Mighty Cam Pro Auto Focus Camera, Integrated LED Ring Light on Post Stand SKU 258-207-570



Macro Zoom Mighty Cam Pro Auto Focus Camera, Integrated LED Ring Light on Double Arm Boom Stand SKU 258-209-534




Macro Zoom EIDOS Camera with 11.6" built-in HD monitor , Integrated LED Ring Light on Post Stand

SKU **260-570-207**



Macro Zoom EIDOS Camera with 11.6" built-in HD monitor, Integrated LED Ring Light on Double Arm Boom Stand SKU 260-534-209







Micro Zoom Mighty Cam USB camera, LED Ring Light on Ultra-Glide Arm Stand

SKU MLS640-244-556



Micro Zoom Mighty Cam USB camera, LED Ring Light on Post Stand

SKU MLS640-244-570



MicroVue Digital Microscope with Built-In 11.6" HD Monitor, LED Ring Light on Track Stand SKU 26700-140



MACRO-MICRO ZOOM VIDEO INSPECTION SYSTEMS

All-in-one camera monitor · Autofocus camera · USB digital camera

	Stand					Illumination				Camera		
MACRO /MICRO ZOOM	Post	Track	Articulating	Double Arm	Ultra Glide	Arbor	Integrated LED Ring	LED Ring	EIDOS	USB 3.0	Auto Focus	MicroVue
258-207-570	•						•				•	
258-209-534				•			•				•	
260-570-207	•						•		•			
260-534-209				•			•		•			
MLS640-244-556					•			•		•		
MLS640-244-570	•							•		•		
26700-140		•						•				•



NEW PRODUCTS INTRODUCTION

MICRO VUE / MIGHTY VUE INSPECTOR



MICRO VUE, DIGITAL MICROSCOPE WITH HD MONITOR











FEATURES:

- · Built-in 11.6" monitor for ergonomic viewing
- · 8x-221x magnification on the built-in monitor
- · HDMI output for external monitor viewing
- · Built-in measurement capabilities
- · Save image/video files to USB storage device
- · USB included
- · Other stands available







11.6" HD Screen

MIGHTY VUE INSPECTOR, MAGNIFIER LAMPS WITH CAMERA



Mighty Vue Inspector 5 D, 2.25x Magnifying Lamp with HD Camera ESD Safe SKU **26512-CAM**



Mighty Vue Inspector 3 D, 1.75x Magnifying Lamp with Built-In HD Camera SKU **26510-CAM**

FEATURES:


- · Built-in HD camera for on-screen viewing
- · Wide lens provides exceptional viewing area
- · MicroSD card save high resolution images and videos
- · USB-C Output connect to your PC



Frosted Diffuser w/ Color Temperature Controls



Tilt the Camera to Adjust the Image On Screen to Your Desired Angle



Inspect Through a Monitor & Magnifying Lens





PROVUE / IN-X MAGNIFYING LAMP





ProVue SuperSlim LED Magnifying Lamp, 5-Diopter [2.25x] SKU 26501-LED



ProVue SuperSlim LED Magnifying Lamp 8-Diopter (3x) SKU 26501-LED-8D



ProVue Deluxe Magnifying Lamp 5 Diopter [2.25x] with White and Amber LEDs SKU 26501-LFL-LED



ProVue Solas Magnifying Lamp XL35 with Interchangeable 5-Diopter Lens [2.25x] SKU 26501-XL35



ProVue Solas XL58 Magnifying Lamp with Interchangeable 8-Diopter Lens [3x] SKU 26501-XL58



In-X Interchangeable Magnifying Lamp with 5 Diopter Lens [2.25x magnification]

SKU 26501-LED-INX

Diopter Magnification

5 Diopter (2.25x magnification) 8 Diopter (3x magnification) 12 Diopter (4x magnification) 15 Diopter (4.75x magnification)











PROVUE / IN-X MAGNIFYING LAMP



	26501-LED	26501-LED-8D	26501-LFL-LED	26501-XL35	26501-XL58	26501-LED-INX
Glass Lens 5", 5 diopter (2.25x magnification)	•		•	•		
Glass Lens 5", 8 diopter (3x magnification)		•		•	•	
Glass Lens 5" 8, 12 and 15 diopeters						
36 High Intensity White LEDs 36 High Intensity Amber LEDs			•			
60 High Intensity White LEDs	•			•	•	
64 High Intensity White LEDs						•
On/Off lighting Control	•					
On/Off brightness adjustment						
On/Off with touch buttons to control the lighting intensity				•	•	•
Arm Lengh max 36"reach						•
Lens Interchangable					•	•
Heavy-Duty 5' cable						
20V power adapter	•					
20V power adapter, Input: AC100V-240V				•	•	•
560 Lumens	•					
800 Lumens				•	•	
950 Lumens						
Color Temperature 6,500K	•	•				
Table Clamp	•	•	•	•	•	



ACCESORIES MAGNIFYING LAMP



Interchangeable Lens for In-X Magnifying Lamps

SKU **26501-INX-RL15D 15D** [4.75x] SKU **26501-INX-RL12D 12D** [4x] SKU **26501-INX-RL8D 8D** [3x] SKU **26501-INX-RL5D 5D** [2.25x]



5 Inch Diameter Replacement Lens for ProVue Magnifying Lamps

SKU **26501-RL8D 8D** [3x] SKU **26501-RL5D 5D** [2.25x] SKU **26501-RL3D 3D** [1.75x]



Replacement Table Clamp for ProVue SuperSlim Magnifying Lamps

SKU 26509-STN Compatible with: 26501-LED, 26501-LED-8D



Replacement Clamp for ProVue Deluxe and Mighty Vue Deluxe Magnifying Lamps

SKU 26509-STN
Compatible with:
26501-LFL-LED



Floor Stand Heavy Duty with Castors

SKU **26509-STN**

Heavy duty weighted stand with 5 full swivel castors for easy mobility. Ideal for use with magnifying lamps that needs to be moved frequently. Pole height is 780mm (30in) and crossbars are 216mm (8.5" long). Will accommodate magnifying lamps with post diameter of max 11.5mm.



Weighted Table Base for ProVue SuperSlim Magnifying Lamp

SKU **26501-WB**

For use with ProVue SuperSlim Magnifying Lamps 26501-LED, 26501-LED-8D.

Mount your ProVue SuperSlim Magnifying Lamp anywhere you need to with this sturdy, secure and durable weighted table base.



Work Bench Mounting Bracket for Magnifying Lamps

SKU **26500-MB1**

Metal work bench mounting bracket for Aven magnifying lamps. 12.7mm opening fits ProVue SuperSlim, Mighty Vue Pro and Mighty Vue Slim magnifying lamps. Includes 3 screws to permanently secure to a work surface.



MIGHTY VUE / OPTIVUE MAGNIFYING LAMP





Mighty Vue Pro 3 Diopter [1.75x] Magnifying Lamp with UV and White LEDs -ESD Safe SKU 26505-ESL-XL3-UV



Mighty Vue Pro 5 Diopter [2.25x] Magnifying Lamp with UV and White LEDs -ESD Safe SKU 26505-ESL-XL5-UV



Mighty Vue Pro 5 Diopter [2.25x] Magnifying Lamp with Color Temperature and Brightness Control - ESD Safe

SKU 26505-ESL-XL5



Mighty Vue Pro 3 Diopter [1.75x] Magnifying Lamp with Color Temperature and Brightness Control

SKU **26505-LED-XL3**



Mighty Vue Slim 5 Diopter [2.25x] LED Magnifying Lamp with Brightness Control

SKU **26505-MX5**



OptiVue 5-Diopter [2.25x] LED Magnification Desk Lamp

SKU **26507-XL5**

SMD LED Illumination











MIGHTY VUE / OPTIVUE MAGNIFYING LAMP



	26505-ESL-XL3-UV	26505-ESL-XL5-UV	26505-ESL-XL5	26505-LED-XL3	26505-MX5	26507-XL5
Glass Lens 4", 5 diopter (2.25x magnification)						
Glass Lens 6.5"x 4", 5 diopter (2.25x magnification)						
Glass Lens 7.5"x 6.2", 3 diopter (1.75x magnification)						
Glass Lens 7.5"x 6.2", 5 diopter (2.25x magnification)		•	•			
30 UV LEDs 400nm UV						
36 High Intensity White LEDs						
48 White LEDs 6500K Color Temperature						
30 High Intensity 3500K LEDs 30 High Intensity 6500K LEDs			•	•		
60 High Intensity White LEDs Max 700lm						
ESD Safe 📤						
On/off switch						
On/Off with brightness and color adjustment						
1-10W Adjustable Brightness						
11" Flexible Gooseneck						
Arm Lengh max 34" reach						
Arm Lengh max 36" reach						
Power adapter						
Input: 100V-240V -50/60Hz						
Max 570 Lumens						
700 Lumens						
Max 1100 Lumens						
Table Clamp						
Heavy-Duty table clamp						



MAGNIFIERS HAND HELD AND HEADBAND





Wide-View Magnifier 2.25x / 4x with Ultraviolet and White LEDs SKU 26060



Hand Held Magnifier 10x/30x with LED Light SKU 26053



Hand Held Magnifier 5x/20x with LED Light SKU 26054



OptiVISOR is a precision binocular headband magnifier

on ocular rieduband magniner			
SKU	26103	Magnifier 2x	
SKU	26104	Magnifier 2.5x	
SKU	26105	Magnifier 2.75x	
SKU	26106	Magnifier 3.5x	



Replacement glass lenses for Aven's OptiVisor headband magnifiers.

11149	1111010.	
SKU	26107	Lens #2 (1.5x)
SKU	26108	Lens #3 (1.75x)
SKU	26109	Lens #4 (2x)
SKU	26110	Lens #5 (2.5x)
SKU	26111	Lens #7 (2.75x)
SKH	26112	Lens #10 (3.5x)



Auxiliary Glass lens for the Optivisor headband magnifier. Increases magnification by 2-1/2x SKU 26113



Headband Magnifier with LEDs light w/5 interchangeable lenses: 1x, 1.5x, 2x, 2.5x, 3.5x SKU 26115



OptiSight Headband Magnifier w/3 interchangeable lenses: 1.75x at 14", 2x at 10" and 2.5x at 8" SKU 26224



OptiVue Headband Magnifier w/ 4 Lenses interchangeable (1.6x, 2.0x, 2.5x, 3.5x)
SKU 26226



MAGNIFIERS HAND HELD





	26060	26053	26054
Glass Lens 93mm x 43mm, 5D (2.25x) with 12 D (4x) Spot Lens	•		
Glass Lens 30mm, 21mm (10x, 30x)		•	
Glass Lens 75mm, 21mm (5x, 20x)			•
26 UV LEDs (8 Watts) 365nm	•		
18 White LEDs 6500K two intensity levels (4 watt)	•		
LED UV or White operation in one Device	•		
36,000+ hours (White LED) 30,000+ hours (UV LED)	•		
6 LED illuminated handheld magnifier		•	
11 total LEDs illuminated handheld magnifier			•
ESD Safe	•		
4000 mAh Rechargeable Lithium Ion Battery	•		
Powered by 3AAA.		•	•
Features an ON/OFF switch button		•	•
Ergonomic designed straight handle		•	•
LEDs provides strong light for clear viewing		•	•



MACHINE LIGHTS TUBULAR LED

LED illumination · Fluid Resistant · Impact Resistant Energy Efficient Dust Proof



































Tubular LED Machine Light 2 X 14 Watt 26 In (658 Mm), Dust Proof, Fluid and Impact Resistant SKU 26600-505





SKU 26600-501

















Tubular LED Machine Light 20 Watt 22.72 In (577mm) with Glass Diffuser. Dust Proof and Fluid Resistant SKU 26600-503G







LED Machine Light 22 In (560mm) 28 Watt, Impact Resistant and Aluminium body SKU 26600-510





LED Illumination



Fluid Resistant



Impact Resistant



Energy Efficient



Dust Proof



MACHINE LIGHTS TUBULAR LED

LED illumination · Fluid Resistant · Impact Resistant · Energy Efficient · Dust Proof

	26600-505	26600-505G	26600-501	26600-503	26600-503G	26600-510
Illuminance 520 lux at 47 inches (1.2 meters)				•	•	
Illuminance 530 lux at 55 inches (1.4 meter)	•	•				
Illuminance 530 lux at 39 inches (1 meter)			•			
Long life LEDs (40,000 hours)	•	•	•	•	•	
Wide Illumination angle	•	•	•	•	•	
IP67 rated	•	•	•	•	•	
Sealed to keep out fluids, chips and shavings	•	•	•	•	•	
Crack resistant durable acrylic diffuser lens	•		•	•		
Glass diffuser lens		•			•	
Built in Ballast	•	•	•	•	•	
28 watt LED Lights, 40,000 hours of life						•
Tempered glass diffuser lens						•
Color Temperature 5600K - 6000K						•
Aluminum body						•





PRECISION TOOLS



ACCU-CUT PRECISION CUTTERS







Oval Head SKU 10821F



Oval Relief Head SKU 10822S

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.25mm

Cutting Edge	Flush
Cutting Capacity	0.15 to 1.25mm

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.2mm





Large Oval Head SKU 10823F

Cutting Edge	Flush
Cutting Capacity	0.15 to 1.1mm

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.5mm

Cutting Edge	Flush
Cutting Capacity	0.15 to 1.5mm





Mini Oval H	ead
SKU 10827F	

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.25mm

Cutting Edge	Flush
Cutting Capacity	0.1 to 0.9mm



Semi-Flush

0.2 to 1.25mm


Cutting Edge

Cutting Capacity

XL C	Oval Head	No.
SKU	10829F	

Cutting Edge	Flush
Cutting Capacity	0.2 to 1.25mm

XL Oval Head SKU 10829F	
Cutting Edge	Eluch





ACCU-CUTPRECISION CUTTERS





Tapered Head SKU 10825F

Таре	ered	Relie	f Head	d
SKU	1082	6S		
			10	19

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.25mm

Cutting Edge	Flush
Cutting Capacity	0.15 to 1.25mm

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.15mm





Mini	Tapered	Head
SKU	10828F	

Cutting Edge	Flush
Cutting Capacity	0.1 to 1.05mm

Cutting Edge	Semi-Flush
Cutting Capacity	0.2 to 1.1mm

Cutting Edge	Flush
Cutting Capacity	0.1 to 1mm





TECHNIK STAINLESS STEEL CUTTERS

400 series Stainless steel ESD grips







Cutting Edge	Semi-Flush
Cutting Capacity	114mm (4.5")

Cutting Edge	Flush
Cutting Capacity	114mm (4.5")

Cutting Edge	Semi-Flush
Cutting Capacity	114mm (4.5")





Cutting Edge	Flush
Cutting Capacity	114mm (4.5")


Cutting Edge	Flush
Cutting Capacity	110mm (4.3")



Cutting Edge	Semi-Flush
Cutting Capacity	114mm (4.5")



Cutting Edge	Semi-Flush
Cutting Capacity	114mm (4.5")





NIPTEC AFFORDABLE CUTTERS

Narrow cutting head · Carbon Steel cutting blades







Cutting Edge	Flush
Cutting Capacity	16 AWG
Jaw Length	0.36 inch

Cutting Edge	Flush
Cutting Capacity	18 AWG
Jaw Length	5/16 inch

Cutting Edge	Flush
Cutting Capacity	16 AWG



Cutting Edge	Semi-Flush
Cutting Capacity	12 AWG
Jaw Length	0.5 inch



Cutting Edge	Flush
Cutting Capacity	22 AWG
Jaw Length	0.36 inch




 Select models with spring-release for reduced hand fatigue

· Lap and rivet joint construction



TECHNIK STAINLESS STEEL PLIERS





SKU 10301

Jaw Style	Smooth
Jaw Length	23.6mm
Head Width	10.78mm
Tip Width	1.6mm

Chain Nose 5" 127mm SKU 10302

Jaw Style	Smooth
Jaw Length	26.6mm
Head Width	11.85mm
Tip Width	1.8mm

Chain Nose 4.5" 114mm

SKU 10307

Jaw Style	Serrated
Jaw Length	23.6mm
Head Width	10.78mm
Tip Width	1.6mm

Chain Nose 5" 127mm

SKU 10308

Jaw Style	Serrated
Jaw Length	26.6mm
Head Width	11.85mm
Tip Width	1.8mm

Chain Nose Extra Long 5" 127mm

SKU 10311

Jaw Style	Smooth
Jaw Length	37.4mm
Head Width	11.85mm
Tip Width	1.8mm

Chain Nose Extra Long 5" 127mm

SKU 10311S

Jaw Style	Serrated
Jaw Length	37.4mm
Head Width	11.85mm
Tip Width	1.8mm

Chain Nose 6" 152mm

SKU 10333

Jaw Style	Serrated
Jaw Length	38.8mm
Head Width	11.85mm
Tip Width	2mm

Flat Nose 4.5" 114mm

SKU 10303

Jaw Style	Smooth
Jaw Length	23.6mm
Head Width	10.78mm
Tip Width	3.2mm

Flat Nose 5" 127mm

SKU **10304**

Jaw Style	Smooth
Jaw Length	29.9mm
Head Width	11.85mm
Tip Width	5.87mm



TECHNIK STAINLESS STEEL PLIERS

400 series Stainless steel · ESD grips



Jaw Style	Smooth
Jaw Length	42mm
Head Width	11.85mm
Tip Width	5.3mm

Round Nose 4.5" 114mm SKU 10305

Jaw Style	Smooth
Jaw Length	21.3mm
Head Width	10.78mm
Tip Width	1.14mm



Jaw Style	Smooth
Jaw Length	23.6mm
Head Width	11.85mm
Tip Width	1.14mm



Jaw Style	Smooth
Jaw Length	60mm
Head Width	10.78mm
Tip Width	1.5mm

	t Nose	4.5"
114r	nm	
SKU	10309	100

Jaw Style	Smooth
Jaw Length	22.8mm
Head Width	10.78mm
Tip Width	1.5mm

Bent 114	t Nose 4.5" mm	W. 55
SKU	10310	


Jaw Style	Serrated
Jaw Length	22.8mm
Head Width	10.78mm
Tip Width	1.5mm



Jaw Style	Smooth
Jaw Length	49mm
Head Width	10.78mm
Tip Width	1.5mm



Jaw Style	Smooth
Jaw Length	40.6mm
Head Width	10.78mm
Tip Width	2mm





TECHNIK STAINLESS STEEL PLIERS

400 series Stainless steel · ESD grips



Jaw Style	Serrated
Jaw Length	49mm
Head Width	10.78mm
Tip Width	1.5mm

Needle Nose Curved 6" 152mm SKU 10953

Jaw Style	Serrated
Jaw Length	31.2mm
Head Width	10.78mm
Tip Width	1.3mm

Long Nose 4.75" 120.5mm SKU 10315

Jaw Style	Serrated
Jaw Length	26.4mm
Head Width	10.78mm
Tip Width	1.8mm





ARTIS ERGONOMIC TWEEZERS

Angle bend provides a softer grip · Stainless steel · ESD safe coating



Tip Style	Straight, Strong, Precise
Length	5 in l 130 mm
Material	Stainless Steel



Tip Style	Straight, Strong, Precise
Length	4 3/4 in I 120 mm
Material	Stainless Steel



Tip Style	Straight, Fine
Length	5 1/4 in l 135 mm
Material	Stainless Steel



Tip Style	Straight, Thick, Flat, Strong
Length	4 1/2 in l 115mm
Material	Stainless Steel



Tip Style	Straight, Fine
Length	4 1/2 in l 115mm
Material	Stainless Steel



Tip Style	Tapered, Sharp
Length	4 1/2 in l 115mm
Material	Stainless Steel



Tip Style	Straight, Ultra Fine
Length	4 1/4 in 110 mm
Material	Stainless Steel



Tip Style	Tapered, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel



Tip Style	Curved Ultra Fine
Length	4 1/2 in l 115mm
Material	Stainless Steel



BLU-TEK TITANIUM NITRIDE TWEEZERS

Durability · Corrosion resistance · Scratch resistance



Tip Style	Straight, Ultra Fine
Length	Tip: 1.18 in 30 mm Total: 4.76 in 121 mm
Material	Stainless Steel treated with Titanium Nitride PVD Infusion Process



Tip Style	Tapered, Ultra Fine
Length	Tip: 1.4 in 36 mm Total: 4.68 in 119 mm
Material	Stainless Steel treated with Titanium Nitride PVD Infusion Process



Tip Style	Angled, Ultra Fine
Length	Tip: 1.38 in 35 mm Total: 4.76 in 121 mm
Material	Stainless Steel treated with Titanium Nitride PVD Infusion Process



Tip Style	Curved Ultra Fine
Length	Tip: 0.55 in 14 mm Total: 4.76 in 121 mm
Material	Stainless Steel treated with Titanium Nitride PVD Infusion Process



Tip Style	Fine Angled
Length	Tip: 0.55 in 14 mm Total: 4.76 in 121 mm
Material	Stainless Steel treated with Titanium Nitride PVD Infusion Process



Stainless Steel · Anti-acid · Anti-magnetic

Tweezer AA Yellow SKU 18013EZ



Tip Style	Straight, Strong, Precise
Length	5 in l 130 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer OO Red SKU 18032EZ



Tip Style	Straight, Thick, Flat, Strong
Length	4 3/4 in l 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 2A Black SKU 18049EZ



Tip Style	Tapered, Sharp
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 3C Light Blue SKU 18056EZ



Tip Style	Straight, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 5 Green SKU 18062EZ



Tip Style	Tapered, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 7 Orange SKU 18072EZ



Tip Style	Curved Ultra Fine
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic





Tweezer OO-SS



SKU	18037-SS	
	OOD-55 anno or	in in

Tweezer OOD-SS 4.75"



Tip Style	Straight, Thick, Flat, Strong
Handles	Smooth
Length	4 3/4 in l 120 mm
Material	400 Stainless Steel

Tip Style	Straight, Thick, Flat, Strong
Handles	Serrated
Length	4 3/4 in l 120 mm
Material	400 Stainless Steel

Tip Style	Straight Fine Serrated
Handles	Serrated
Length	6 7/8 in I 175mm
Material	400 Stainless Steel

Splinter Forcep 4-1/2" SKU **18439**



Forc	ep 5"	
Strai	ght Serrated	
SKU	18436	

Forc	ep 6"	w/Alignment	Pin
SKU	18401		



SNU	18401	
	#	

Tip Style	Straight Serrated
Handles	Serrated
Length	4-1/2 in l 115 mm
Material	400 Stainless Steel

Tip Style	Straight Serrated
Handles	Serrated
Length	5 in I 130 mm
Material	400 Stainless Steel

Tip Style	Straight Serrated
Handles	Serrated
Length	6 in I 150 mm
Material	400 Stainless Steel

Tapered Tweezer 4-3/8" SKU **18482**




Tip Style	Tapered, Smooth
Handles	Smooth
Length	4 3/8 in l 110 mm
Material	400 Stainless Steel

Blunt Tweezer 5-15/16" SKU **18490**



Tip Style	Blunt, Rounded
Handles	Serrated
Length	5 15/16 in I 150 mm
Material	400 Stainless Steel







Self Locking Tweezer 4-1/2" Narrow Short



	Locking ght Nar	Tweezer 6-1/2" row
SKU	18419	18.419 (

Self Locking Tweeze	r 6-1/2"
Fiber Grip	



Tip Style	Straight, narrow smooth
Handles	Self Locking
Length	4-1/2 in l 114 mm
Material	400 Stainless Steel

Tip Style	Straight Narrow Smooth
Handles	Self Locking
Length	6-1/2 in l 165 mm
Material	400 Stainless Steel

Tip Style	Straight, Smooth
Handles	Self Locking
Length	6-1/2 in l 165 mm
Material	400 Stainless Steel

Mini Tweezer 3-1/2" Round Tips



Tip Style	Blunt, Smooth, rounded
Handles	Serrated
Length	3.5 in 88.9 mm
Material	400 Stainless Steel

Forcep 6" Straight Serrated



Tip Style	Straight Serrated
Handles	Serrated
Length	6 in I 155 mm
Material	400 Stainless Steel

Forcep 8" Straight Serrated



Tip Style	Straight Serrated
Handles	Serrated
Length	8 in I 200 mm
Material	400 Stainless Steel

Forcep 10" Straight Serrated



Tip Style	Straight Serrated
Handles	Serrated
Length	10 in l 255 mm
Material	400 Stainless Steel

Forcep 12" Straight Serrated



Tip Style	Straight Serrated
Handles	Serrated
Length	12 in I 300 mm
Material	400 Stainless Steel

Self Locking Tweezer 6-1/4" Wide Tips



Tip Style	Straight Wide Serrated
Handles	Self Locking
Length	6-1/4 in I 160 mm
Material	400 Stainless Steel





Forcep 8" **PVC Plastic Coated Tips**



Tip Style	Plastic Coated
Handles	Serrated
Length	8 in I 200 mm
Material	400 Stainless Steel, Plastic Coated

Forceps 12" **PVC Plastic Coated Tips**



Tip Style	Plastic Coated
Handles	Serrated
Length	12 in I 300 mm
Material	400 Stainless Steel, Plastic Coated

Smooth Tweezer 4-3/4" Flat Tips



Tip Style	Smooth Flat
Handles	Serrated
Length	4-1/2 in I 114.3 mm
Material	400 Stainless Steel

Mini Blunt Tweezer 3-1/2" Flat Tips



Tip Style	Straight Flat Tips
Handles	Smooth
Length	3 1/2 in I 90 mm
Material	400 Stainless Steel

Mini Blunt Tweezer 3-1/8" **Round Tips**



Tip Style	Blunt, Smooth, rounded
Handles	Serrated
Length	3 1/8 in l 80 mm
Material	400 Stainless Steel

Mini Blunt Tweezer 3-1/8" **Angled Flat Tips**



Tip Style	Flat, straight
Handles	Serrated
Length	3 1/8 in I 80 mm
Material	400 Stainless Steel

Offset Spade Tweezers 4-1/8"



Tip Style	Spade
Handles	Serrated
Length	4 3/4 in I 120 mm
Material	400 Stainless Steel

Spade Tweezers 4-3/8"



Tip Style	Spade
Handles	Serrated
Length	4 3/8 in l 110 mm
Material	400 Stainless Steel

Toothed Tissue Forcep 5-1/2"



Tip Style	Straight Toothed
Handles	Serrated
Length	5-1/2 in I 140 mm
Material	400 Stainless Steel



TECHNIK PRECISION TWEEZERS





Tip Style	Straight, Strong, Precise
Length	5 in l 130 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Straight, Strong, Precise
Length	5 in l 130 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Straight, Fine
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Straight, Thick, Flat, Strong
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic




Tip Style	Straight, Thick, Flat, Strong
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Straight, Thick, Flat, Strong
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Straight, Fine
Length	5 1/2 in l 140 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic





TECHNIK PRECISION TWEEZERS

Stainless/Steel · Anti-acid · Anti-magnetic

Tweezer 0C-SA SKU 18029USA



Tip Style	Straight, Fine
Length	3 1/2 in I 90 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Straight, Fine
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Tip Style	Tapered, Sharp
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 2A-SA SKU 18049USA



Tip Style	Tapered, Sharp
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 2AB-SA SKU 18050USA



Tip Style	Curved, Flat
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 3-SA



Tip Style	Straight, Ultra Fine
Length	4 7/8 in l 125 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 3C-SA SKU 18056USA



Tip Style	Straight, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 4-SA SKU 18059USA



Tip Style	Tapered, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 5-SA



Tip Style	Tapered, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic



Stainless/Steel · Anti-acid · Anti-magnetic

Tweezer 5A-SA SKU **18065USA**



Tip Style	Angled, Ultra Fine
Length	4 1/2 in l 115 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 5B-SA SKU **18066USA**



Tip Style	Angled, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 6-SA



Tip Style	Angled, Fine
Length	4 1/4 in l 110 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 7-SA SKU 18072USA



Tip Style	Curved Ultra Fine
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 7B-SA SKU **18074USA**




Tip Style	Curved Ultra Fine
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic

Tweezer 35A-SA



Tip Style	Straight, Broad
Length	4 3/4 in I 120 mm
Material	Stainless Steel, Anti-acid and Anti-magnetic







Curved Tweezers 4-3/8" SKU 18481



Tip Style	Curved, Serrated
Handles	Smooth
Length	4 3/8 in l 110 mm
Material	400 Stainless Steel

Forceps 10" Bent end Serrated



Tip Style	Blunt, Bent, Serrated
Handles	Serrated
Length	10 in l 255 mm
Material	400 Stainless Steel

Forceps 12" Bent end Serrated



Tip Style	Bent Serrated
Handles	Serrated
Length	12 in I 305 mm
Material	400 Stainless Steel

Offset Spade Tweezer 4 1/2" SKU 18491



Tip Style	Spade Offset
Handles	Serrated
Length	Offset: 4 1/2 in Total Length: 5 in
Material	400 Stainless Steel

Forceps 6" w/Alignment Pin Curved Serrated



Tip Style	Curved Serrated
Handles	Serrated
Length	6 in I 150 mm
Material	400 Stainless Steel

Forceps 6" w/Alignment Pin Offset Curved Serrated



Tip Style	Offset Curved Serrated
Handles	Serrated
Length	6 in I 150 mm
Material	400 Stainless Steel

Forceps 4-1/2"w/Alignment Pin Bent Tips



Tip Style	Bent, narrow, serrated
Handles	Serrated
Length	4-1/2 in l 114 mm
Material	400 Stainless Steel

Forceps 6" w/Lock Bent SKU 18400



Tip Style	40° Bent serrated
Handles	Serrated, with lock
Length	6 in I 150 mm
Material	400 Stainless Steel

Self Locking Tweezers 6-1/2" Fiber Grip, Bent Tips

SKU **18417**



Tip Style	35° Bent Smooth
Handles	Serrated
Length	6-1/2 in I 165 mm
Material	400 Stainless Steel



TITANIUM TECHNIK PRECISION TWEEZERS

Fully non-magnetic · Corrosion resistant Bio-compatible · Lightweight

2A TITANIUM







Tip Style	Straight, Strong, Precise
Length	5 in l 130 mm
Material	Titanium

Tip Style	Straight, Thick, Flat, Strong
Length	4 3/4 in l 120 mm
Material	Titanium

Tip Style	Straight, Thick, Flat, Strong
Length	4 3/4 in l 120 mm
Material	Titanium





Tweezer 2A
SKU 18049TT
na n


Tip Style	Straight, Fine
Length	4 1/2 in l 115 mm
Material	Titanium

Tip Style	Tapered, Sharp
Length	4 3/4 in l 120 mm
Material	Titanium

Tip Style	Tapered, Sharp
Length	4 1/2 in l 115 mm
Material	Titanium



Tip Style	Straight, Ultra Fine
Length	4 7/8 in l 125 mm
Material	Titanium





TITANIUM TECHNIK PRECISION TWEEZERS

Fully non-magnetic · Corrosion resistant Bio-compatible · Lightweight

2A TITANIUM





iwe	ezer 4	
SKH	18059TT	
3110	1003311	
		TITANUM



Tip Style	Straight, Ultra Fine
Length	4 1/4 in I 110 mm
Material	Titanium

Tip Style	Tapered, Ultra Fine
Length	4 1/4 in l 110 mm
Material	Titanium

Tip Style	Tapered, Ultra Fine
Length	4 1/4 in I 110 mm
Material	Titanium

Tweezer 5A SKU 18065TT



Tip Style	Angled, Ultra Fine
Length	4 1/2 in l 115 mm
Material	Titanium

Tweezer 6
SKU 18069TT



Tip Style	Angled, Fine
Length	4 1/4 in l 110 mm
Material	Titanium

Tweezer 7
SKU 18072TT



Tip Style	Curved Ultra Fine
Length	4 3/4 in I 120 mm
Material	Titanium

Handles



Smooth





STAINLESS STEEL PLIERS AND CUTTERS



Corrosion resistant · Stainless Steel deal for use in a sterile environment

Slip Joint Pliers 6.5" SKU **10370**



Overall Length	6.5 in
Jaw Cap	0.78 in
Material	400 Series Stainless Steel

Slip Joint Pliers W/Plastic Handles 6.5 "




Overall Length	6.5 in
Jaw Length	0.78 in
Material	400 Series Stainless Steel

Grove Joint Pliers 9.5"



Overall Length	9.5 in
Jaw Length Width	0.98 in I 1.18 in
Material	400 Series Stainless Steel




Long Nose Pliers 6" with Wire Cutter SKU 10360



Overall Length	6 in
Jaw Length Width	1.5 in 0.118 in
Material	400 Series Stainless Steel

Long Nose Pliers 6" W/Wire Cutter & Comfort Grip Handle SKU 10360-ER



Stainless Steel

Material

Combination Pliers 8" with Wire Cutter



Overall Length	8 in
Jaw Length Width	1.0 in 0.4 in
Material	400 Series Stainless Steel

Combination Pliers 8" W/Wire **Cutter & Plastic Handles**




Overall Length	8 in
Jaw Length Width	1.01 in 0.4 in
Material	400 Series Stainless Steel





STAINLESS STEEL PLIERS AND CUTTERS

Corrosion resistant · Stainless Steel Ideal for use in a sterile environment





Overall Length	6 in
Jaw Length Width	1.65 in 0.78 in
Material	400 Series Stainless Steel



Overall Length	7 in
Material	Body and Springs: 304 non-magnetic Stainless Steel
	Jaws: 420 Series Stainless Steel



Overall Length	9 in
Material	Body and Springs: 304 non-magnetic stainless steel
	Jaws: 420 Series Stainless Steel

Diagonal Cutter High Leverage



Overall Length	4 in
Jaw Cap	0.5 in
Material	304 Series Stainless Steel

Diagonal Cutter



Overall Length	6 in
Jaw Cap	15/16 in
Material	304 Series Stainless Steel


Diagonal Cutter W/Comfort Grip Handles 6.25"

SKU 10355-ER



Overall Length	8 in
Jaw Cap	1 1/8 in
Material	304 Series Stainless Steel

Pliers Set Stainless Steel SKU 1038



Contains	9 1/2" Grove-Joint Plier, 8" Combination Plier, 6" Long-Nose Plier, 6" Slip-Joint and 6" Wire-Cutting
Material	400 Series Stainless
iviateriai	Steel





STAINLESS STEEL COMBINATION WRENCHES

Rust resistant · 304 Series Stainless Steel Can be autoclaved to temperatures up to 250 °F

Combination Wrench 7/16" SKU 21187-0716



Overall Length	6 1/16 in
Angle	15°
Material	304 Series Stainless Steel

Combination Wrench 1/2" SKU 21187-0102



Overall Length	6 7/8 in
Angle	15°
Material	304 Series Stainless Steel

Combination Wrench 9/16" SKU 21187-0916



Overall Length	7 5/16 in
Angle	15°
Material	304 Series Stainless Steel

Combination Wrench 5/8" SKU 21187-0508



Overall Length	8 1/16 in
Angle	15°
Material	304 Series Stainless Steel

Combination Wrench 3/8" SKU 21187-0308



Overall Length	5 11/16 in
Angle	15°
Material	304 Series Stainless Steel

Combination Wrench 5/16" SKU 21187-0516



Overall Length	5 1/8 in
Angle	15°
Material	304 Series Stainless Steel

Combination Wrench Set 6pc SKU 21187-105



Contains	1/2, 3/8, 5/8, 5/16, 7/16 and 9/16 in
Angle	15°
Material	304 Series Stainless Steel





STAINLESS STEEL ADJUSTABLE WRENCHES

Corrosion resistant · 304 Series Stainless Steel

Adjustable Wrench 4" SKU ST8115-1002



Overall Length	4 in
Jaw Cap	0.5 in
Material	304 Series Stainless Steel

Adjustable Wrench 6" SKU ST8115-1004



Overall Length	6 in
Jaw Cap	15/16 in
Material	304 Series Stainless Steel

Adjustable Wrench 8" SKU ST8115-1006



Overall Length	8 in
Jaw Cap	1 1/8 in
Material	304 Series Stainless Steel

Adjustable Wrench 10" SKU ST8115-1008



Overall Length	10 in
Jaw Cap	1 5/16 in
Material	304 Series Stainless Steel

Adjustable Wrench 12" SKU ST8115-1010



Overall Length	12 in
Jaw Cap	1 1/2 in
Material	304 Series Stainless Steel

Adjustable Wrench 14" SKU ST8115-1012



Overall Length	14 in
Jaw Cap	2.25 in
Material	304 Series Stainless Steel

Adjustable Wrench 17" SKU ST8115-1014



Overall Length	17 in
Jaw Cap	2.35 in
Material	304 Series Stainless Steel

Adjustable Wrench 23" SKU ST8115-1016



Overall Length	23 in
Jaw Cap	2.36 in
Material	304 Series Stainless Steel



STAINLESS STEEL ADJUSTABLE WRENCHES

Corrosion resistant · 304 Series Stainless Steel

Adjustable Wrench 4" with PVC Grip
SKU ST8115-1002G



Overall Length	4 in
Jaw Cap	0.5 in
Material	304 Series Stainless Steel

Adjustable Wrench 6" with PVC Grip SKU ST8115-1004G



Overall Length	6 in
Jaw Cap	15/16 in
Material	304 Series Stainless Steel

Adjustable Wrench 8" with PVC Grip
SKU ST8115-1006G



Overall Length	8 in
Jaw Cap	1 1/8 in
Material	304 Series Stainless Steel

Adjustable Wrench 10" with PVC Grip
SKU ST8115-1008G



Overall Length	10 in
Jaw Cap	1 5/16 in
Material	304 Series Stainless Steel

Adjustable Wrench 12" with PVC Grip SKU ST8115-1010G



Overall Length	12 in
Jaw Cap	1 1/2 in
Material	304 Series Stainless Steel

Adjustable Wrench 14" with PVC Grip
SKU ST8115-1012G



Overall Length	14 in
Jaw Cap	2.25 in
Material	304 Series Stainless Steel

Adjustable Wrench 17 with PVC Grip
SKU ST8115-1014GV



Overall Length	17 in
Jaw Cap	2.35 in
Material	304 Series Stainless Steel

Adjustable Wrench 23" with PVC Grip
SKU ST8115-1016G



Overall Length	23 in
Jaw Cap	2.36 in
Material	304 Series Stainless Steel





NAME: QWEB

EMAIL: QWEB@QSOURCE.COM