# **SAFETY DATA SHEET**



### Trace Technologies Conformal Coating Remover

Section 1. Identi	fication
GHS product identifier	: Trace Technologies Conformal Coating Remover
Product code	: 2510-N
Other means of identification	: Remover.
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Not applicable.	
Supplier's details	: Techspray 8125 Cobb Center Drive Kennesaw, GA 30152 Tel:678-819-1408 Toll free: 800-858-4043 Fax: 806-372-8750
Emergency telephone number (with hours of operation)	: Chemtrec - 1-800-424-9300 CANUTEC (Canadian Transportation): (613) 996-6666 Emergency phone: (800) 858-4043 24/7
Section 2. Hazar	ds identification
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>Highly flammable liquid and vapor.</li> <li>Harmful if swallowed.</li> </ul>
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	: IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Storage	: Store in a well-ventilated place. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.



# Section 3. Composition/information on ingredients

### Substance/mixture Other means of

: Mixture

- identification
- : Remover.

Ingredient name	%	CAS number
tetrahydrofuran	≥90	109-99-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

**Description of necessary first aid measures** 

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptom	s/effects, acute and delayed
Potential acute health et	ffects
Eye contact	: May cause eye irritation.
Inhalation	: At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen.
Skin contact	: May cause skin irritation.
Ingestion	: Harmful if swallowed.
Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation redness watering

2/12

# Section 4. First aid measures

Inhalation	: Adverse symptoms may include the following: dizziness/vertigo drowsiness/fatigue headache nausea or vomiting unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: Adverse symptoms may include the following: stomach pains nausea or vomiting
Indication of immediate m	edical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialis

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency	: No action shall be taken involving any personal risk or without suitable training.
personnel	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from
	entering. Do not touch or walk through spilled material. Shut off all ignition sources.
	No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide
	adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

# Section 6. Accidental release measures

For emergency responders	-	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### Control parameters

Occupational exposure limits

# Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
tetrahydrofuran	ACGIH TLV (United States, 3/2015). Absorbed through skin. STEL: 100 ppm 15 minutes. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2013). STEL: 735 mg/m <sup>3</sup> 15 minutes. STEL: 250 ppm 15 minutes. TWA: 590 mg/m <sup>3</sup> 10 hours. TWA: 200 ppm 10 hours. OSHA PEL (United States, 2/2013). TWA: 590 mg/m <sup>3</sup> 8 hours. TWA: 200 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). STEL: 735 mg/m <sup>3</sup> 15 minutes. STEL: 735 mg/m <sup>3</sup> 15 minutes. TWA: 590 mg/m <sup>3</sup> 8 hours. TWA: 590 mg/m <sup>3</sup> 8 hours. TWA: 590 mg/m <sup>3</sup> 8 hours. TWA: 200 ppm 15 minutes. STEL: 250 ppm 15 minutes. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventil other engineering controls to keep worker exposure to airborne contaminants bel recommended or statutory limits. The engineering controls also need to keep ga vapor or dust concentrations below any lower explosive limits. Use explosion-proventilation equipment.	ow any s,
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ens they comply with the requirements of environmental protection legislation. In son cases, fume scrubbers, filters or engineering modifications to the process equipn will be necessary to reduce emissions to acceptable levels.	ne
Individual protection measure	<u>S</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, be eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and s showers are close to the workstation location.	ng.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risl assessment indicates this is necessary to avoid exposure to liquid splashes, mist gases or dusts. If contact is possible, the following protection should be worn, ur the assessment indicates a higher degree of protection: safety glasses with side shields.	s, less
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard sho worn at all times when handling chemical products if a risk assessment indicates necessary. Considering the parameters specified by the glove manufacturer, che during use that the gloves are still retaining their protective properties. It should that noted that the time to breakthrough for any glove material may be different for dif- glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	this is eck be ferent
Body protection	: Personal protective equipment for the body should be selected based on the task performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear static protective clothing. For the greatest protection from static discharges, cloth should include anti-static overalls, boots and gloves.	anti-
Other skin protection	: Appropriate footwear and any additional skin protection measures should be sele based on the task being performed and the risks involved and should be approve specialist before handling this product.	

## Section 8. Exposure controls/personal protection

### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	1	Liquid.
Color	1	Clear. Colorless.
Odor	1	Aromatic.
Odor threshold	1	Not available.
рН	1	Not available.
Melting point	1	Not available.
Boiling point	1	Not available.
Flash point	1	Closed cup: -14.4°C (6.1°F) [Tagliabue.]
Evaporation rate	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Lower: 2% Upper: 11.8%
Vapor pressure	1	17.3 kPa (130 mm Hg) [room temperature]
Vapor density	1	2.5 [Air = 1]
Relative density	1	Not available.
Solubility	1	Not available.
Solubility in water	1	Not available.
Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	1	321°C (609.8°F)
Decomposition temperature	1	Not available.
Viscosity	1	Not available.
Flow time (ISO 2431)	1	Not available.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	]
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.	
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials	
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products shou not be produced.	ld

6/12

# Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
tetrahydrofuran	LD50 Oral	Rat	1650 mg/kg	-

### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>its</u>
Eye contact	: May cause eye irritation.
Inhalation	: At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen.
Skin contact	: May cause skin irritation.
Ingestion	: Harmful if swallowed.
Eye contact	<ul> <li>hysical, chemical and toxicological characteristics</li> <li>Adverse symptoms may include the following: pain or irritation redness watering</li> </ul>
Inhalation	: Adverse symptoms may include the following: dizziness/vertigo drowsiness/fatigue headache nausea or vomiting unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness dryness

cracking

# Section 11. Toxicological information

1.00		
IN	destion	
	gootion	

: Adverse symptoms may include the following: stomach pains nausea or vomiting

Delayed and immediate effec	ts :	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ct	<u>5</u>
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
<b>Developmental effects</b>	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

### Numerical measures of toxicity

Acute toxicity	<u>y estimates</u>
----------------	--------------------

Route	ATE value
Oral	1692.3 mg/kg

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
tetrahydrofuran	Acute LC50 2160000 to 2360000 μg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 367 mg/l Fresh water	Fish - Pimephales promelas - Embryo	33 days

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
tetrahydrofuran	0.45	-	low

#### Mobility in soil

Other adverse effects

Soil/water partition : Not available. coefficient (Koc)

: No known significant effects or critical hazards.

Date of issue/Date of revision	: 10/3/2018	Date of previous issue	: No previous validation	Version : 1	8/12

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #		Reference number
Tetrahydrofuran (I); Furan, tetrahydro-(I)	109-99-9	Listed	U213

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	ΙΑΤΑ
UN number	-	-	-	UN2056	UN2056	UN2056
UN proper shipping name	Consumer commodity ORM-D	Consumer commodity ORM-D	Consumer commodity ORM-D	Tetrahydrofuran (tetrahydrofuran)	Terahydrofuran (tetrahydrofuran)	Tetrahydrofuran (tetrahydrofuran)
Transport hazard class(es)	ORM-D	ORM-D	ORM-D	3	3	3
Packing group	-	-	-	-	II	11
Environmental hazards	No.	No.	No.	No.	No.	No.
Additional information	Reportable quantity 1025.6 lbs / 465.64 kg [138. 84 gal / 525.55 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2. 18-2.19 (Class 3).			-	Excepted Quantity

Trace Technologies Conformal Coating Remover					
Section 14. Trans	ort inforn	nation			
exemption CFR 173. (1).					
Special precautions for use	upright and s		at persons trans		d containers that are uct know what to do in the
Fransport in bulk according o Annex II of MARPOL and he IBC Code	Not available	9.			
Section 15. Regul	ory infor	mation			
J.S. Federal regulations	TSCA 8(a) C	AIR: tetrahydrofu DR Exempt/Part es inventory (TS	tial exemption:		d or exempted.
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Not listed				
Clean Air Act Section 602 Class I Substances	Not listed				
Clean Air Act Section 602 Class II Substances	Not listed				
DEA List I Chemicals (Precursor Chemicals)	Not listed				
DEA List II Chemicals (Essential Chemicals)	Not listed				
<u>SARA 302/304</u>					
Composition/information	<u>ingredients</u>				
No products were found.					
SARA 304 RQ	Not applicabl	le.			
SARA 311/312 Classification	Fire hazard Immediate (a	acute) health haza	ard		
	· · · ·	,			

### Composition/information on ingredients

Name	%		Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
tetrahydrofuran	≥90	Yes.	No.	No.	Yes.	No.

### **State regulations**


BUTYLENE OXIDE			
1,4-EPOXYBUTANE			
)-			
Chemical Weapon Convention List Schedules I, II & III Chemicals			

# Section 15. Regulatory information

Montreal Protocol (Annexes A, B, C, E) Not listed.					
Stockholm Convention on Persistent Organic Pollutants Not listed.					
Rotterdam Conver Not listed.	ntion on Prior Informed Consent (PIC)				
UNECE Aarhus Pro Not listed.	otocol on POPs and Heavy Metals				
International lists National inventory					
Australia	: All components are listed or exempted.				
Canada	: All components are listed or exempted.				
China	: All components are listed or exempted.				
Europe	: All components are listed or exempted.				
Japan	<ul> <li>Japan inventory (ENCS): All components are listed or exempted.</li> <li>Japan inventory (ISHL): Not determined.</li> </ul>				
Malaysia	: All components are listed or exempted.				
New Zealand	: All components are listed or exempted.				
Philippines	: All components are listed or exempted.				
Republic of Korea	: All components are listed or exempted.				
Taiwan	: All components are listed or exempted.				
Turkey	: All components are listed or exempted.				

# Section 16. Other information

#### Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

11/12

# Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### Procedure used to derive the classification

	JustificationOn basis of test dataCalculation method		
FLAMMABLE LIQUIDS - Ca ACUTE TOXICITY (oral) - (			
History			
Date of printing	: 10/3/2018		
Date of issue/Date of revision	: 10/3/2018		
Date of previous issue	: No previous validation		
Version	: 1		
Key to abbreviations	IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition co MARPOL = International Convention for the Prevention	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)	
References	: Not available.		

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.