SCS Dissipative Anti-Fatigue Rubber mats meet ANSI/ESD S20.20 tested per worksurface standard ANSI/ESD S4.1 and ESD TR53. They are suitable for assembly lines and other workplaces to reduce worker fatigue from jobs that require standing for long periods of time. These durable mats feature a slip-resistant surface with patterned texture. They are easy to clean and resist most common fluids.



RoHS 3. REACH, and Conflict Minerals Statement

None of the RoHS 3 restricted materials or REACH substances of very high concern as of 2018/08/01, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive (EU) 2015/853 ammending Annex II of the RoHS 2 Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See SCS Warranty, Limitation of Liability and Remedies

Specifications and procedures subject to change without notice.

SCS

Features:

- Black rubber ESD floor mat with high-visibility yellow stripe border
- Dissipative black rubber material reduces charge generation and provides an electrical path-to-ground
- Durable material provides excellent abrasion resistance
- · Ground using the installed snaps, or placing on top of ESD flooring
- Patterned texture provides slip-resistant surface
- Meets ANSI/ESD S20.20 tested per worksurface standard ANSI/ESD S4.1 and ESD TR53
- Made in Mexico

Properties	Typical Value
Material	Rubber
Color*	Black with Yellow Stripe Border
Thickness	0.6" (14mm)
Electrical Resistance Black Rubber Yellow Stripe	Surface to Ground (Rtg) 1 x 10^5 to < 1 x 10^9 ohms < 1 x 10^{11} ohms
Tolerance	Width ± 5mm Length ±5mm

^{*}Color and texture may vary between lots and mills

Cleaning Instructions:

Clean with a damp cloth. Do not expose to chemical agents or aggressive substances.

Floor Mat Item Numbers with Hardware

Size	Part No.
0.6" x 2' x 3' (1.5cm x 0.6m x 0.9m)	<u>770120</u>

Included:

- 1 Dissipative Rubber Floor Mat
- 2 10mm Female Snaps (installed)

DISSIPATIVE ANTI-FATIGUE RUBBER FLOOR MAT

DRAWING NUMBER 770120 May 2022