



# ST35

## Soldering Station



### Cost-Effective SensaTemp® Soldering Station

The ST35 Soldering Station is our most cost-effective digital soldering station. Its rugged design and ease of use makes it an ideal soldering system for any operator or DIY enthusiast. The ST35 features PACE's renowned SensaTemp® closed-loop temperature control technology, which maximizes heat delivery at safe, low temperatures, while maintaining unparalleled temperature accuracy and stability. The ST35 is compact and stackable to ensure an efficient workspace.

- Standard Packout Includes PS-90 High Capacity Soldering Iron.
- Password Protected & Temperature Adjustment Lockout
- Auto-Off Safety System

Specifications	ST 35	ST 35 E
<b>Kit with Handpieces Part Numbers:</b>	8007-0599 (PS-90)	8007-0600 (PS-90)
<b>Power Source Only Part Numbers:</b>	8007-0601	8007-0602
<b>Power Requirements</b>	115 VAC, 50/60 Hz (120 Watts Maximum)	230 VAC, 50/60 Hz (120 Watts Maximum)
<b>SensaTemp® Compatibility</b>	SensaTemp® Technology	
<b>Dimensions</b>	104mm (4.1") H x 130mm (5.1") W x 152mm (6.0") D	
<b>Weight</b>	2.3 Kgs (5 lbs.)	
<b>Tip to Ground Resistance</b>	< 2 Ohms	
<b>Temperature Accuracy</b>	Meets or exceeds ANSI-J-STD 001	



# PACE®



# ST125

## Rework Station

### Digital Sensatemp Rework System with Hi-Flo Snap-Vac® Pump

The ST 125 is ideal for users dealing with a wide range of applications. With this system, you can solder, desolder, and remove components using a variety of Sensatemp® powered handpieces. The system comes standard with PACE's patented Hi-Flo Snap-Vac® Pump technology to ensure quick, clean removal of solder from any through-hole joint or surface land. The Hi-Flo pump is so powerful that you won't lose vacuum in continuous use applications. With its simple digitally controlled design and durable yet compact frame, the ST125 can be the most valuable system on your workbench today.



- Standard Packout Includes SX-100 Sodr-X-Tractor
- User defined operating temperature range
- Patented SnapVac® Technology
- ESD Safe Metal Housing

Specifications	ST 125	ST 125 E
<b>Kit with Handpieces Part Numbers:</b>	8007-0607 (SX-100)	8007-0608 (SX-100)
<b>Power Source Only Part Numbers:</b>	8007-609	8007-0610
<b>Power Requirements</b>	97-127 VAC, 50/60Hz (120 Watts Maximum)	230 VAC, 50/60 Hz (120 Watts Maximum)
<b>SensaTemp® Compatibility</b>	SensaTemp® Technology	
<b>Vacuum/Pressure Source Type</b>	Self Contained Pump	
<b>Vacuum (Nominal)</b>	20 in Hg Max	
<b>Pressure (Nominal)</b>	18 p.s.i.	



# PACE®