


SDV 46



TECHNICAL DATA

External dimensions:	(W x H x D) 750 x 410 x 630 mm
Internal dimensions:	(W x H x D) 650 x 210 x 475 mm
Seal length	460 mm
Vacuum pump	21 m ³ /h
Weight:	95 kg
Digital control	Z3000
Power supply:	1 phase, 230 V, 50 Hz

SEALING SYSTEM



SDV SERIES

Our line of ESD vacuum packaging machines is particularly suitable for being used in ESD protected areas.

The controlled reduction of humidity and of oxygen content ensures secure storage and transport conditions.

An ideal packaging solution for moisture-sensitive materials.

Z3000 SENSOR CONTROL

Our sensor control is equipped with a vacuum sensor, and make it possible to set precisely all important parameters.

Humidity and oxygen content can be reduced accurately controlled. 99 memory locations facilitate the repetition of your packaging results and ensure easy handling and operation.



STANDARD FEATURES

SEALING SYSTEM



- Double-seam sealing as standard: aluminium bag with vapour barrier up to thicknesses of 180 micron quickly and reliably sealed.
- Plug-in system for the sealing bars, secure fastening without cables.
- High-pressure sealing: sealing is assisted by the increased clamping pressures. The seam temperature remains stable and generates a clean sealing imprint without temperature loss. Ideal for gentle handling of your consumables and packaging materials.

FURTHER EQUIPMENT FEATURES



- Acrylic cover in anti-static design.
- Alternating current version with 230 V as standard.
- Step vacuum function for high-outgassing products and reduction of the air humidity and the oxygen content.
- Service function: promotes the long life of the machine and optimises service intervals.
- Initial supply of consumables (Teflon tape, sealing wire) included.
- High-quality Busch vacuum pump with spareparts guarantee.

Z3000 DIGITAL CONTROL



- Sensor controlled Z2001 digital control with large vacuum display.
- User friendly
- Service program for the longevity of the machine.
- 99 program memories

CHAMBER AND SHELVES



- Robust technology in stylish finish made of extremely high-quality stainless steel.
- Insertion plates for level adjustment, stylish finish with rounded corners in anti-static design, dissipative, discharge resistor 10⁶ Ohm/sq.
- Teflon coated, sealing materials, adhesives comply with DIN EN 61340-5-2.
- Optimal cleaning, designed according to HACCP guidelines.

SDV 46 FEATURES



Trolley for SDV 46



TECHNICAL DATA

External dimensions: (W x H x D) 730 x 590 x 620 mm
Weight: 28 kg
Vacuum Machine: SDV 46

STAINLESS STEEL




Our sturdily constructed undercarriages are made of stainless steel. Smooth surfaces and rounded edges make them easy to clean.

STABILITY



Secure positioning of the machine is ensured by indentations in the base of the undercarriage. These are based on the size of the machine's rubber feet and prevent the vacuum machine from slipping.

STORAGE COMPARTMENTS



The undercarriage includes two integrated compartments for the storage of your moisture barrier bags so they can be stored in the vicinity of the workstation.

CASTORS



The undercarriage has four stainless steel castors. The two parking brakes ensure optimum fixing of the mobile unit and guarantee a secure base for your vacuum machine.



Totech Europe BV
+31 (0) 38 20 3 1051
sales@totech.eu
www.totech.eu

Member of the ASYS Group