STATGUARD FLOORING TECHNICAL BULLETIN TB-5032

8400 Series - ESD Vinyl Floor Tile Maintenance

Carefully read and follow all product literature including all safety, health and environmental information found in the material safety data sheet and/or product label of chemicals prior to handling or use.

Daily Floor Maintenance

Prevent Dirt and Wear

Install Entrance Matting System at all Entry Doors

Remove Dust and Debris

Sweep or dry mop daily with untreated dust mop

Clean

Damp mop as needed

Normal Cleaning

For Dirt. Grime and Scuff Marks

Use Low-Speed Swing Buffer or Automatic Scrubber

Recommended Cleaning Pad:

Red Buffer Pad

Heavy Cleaning

For Tough Marks

Use Low-Speed Swing Buffer or Automatic Scrubber

Use Recommended Cleaning Pad:

- Blue Cleaner Pad
- Green Scrub Pad
- Brown Stripper Pad*

*Liberally apply cleaning solution when using the Brown Stripper Pad to avoid damaging floor.

Low-Speed Swing Buffer

- 1. Apply 10:1 diluted Statguard Neutral Cleaner (46032/46033) with mop
- 2. Scrub with appropriate cleaning pad
- 3. Damp mop to wipe up soiled solution
- 4. Damp mop with clean solution
- 5. Allow to dry completely
- 6. If tough marks remain, repeat "Normal Cleaning" process using the same pad or switch to a recommended "Heavy Cleaning" pad

Automatic Scrubber

- 1. Fill solution tanks with 5:1 diluted Statguard Stripper (46020/46021)
- 2. Install proper pads on machine
- 3. Scrub floor and pick up dirty solution (automatic)
- 4. Damp mop with clean solution if necessary
- 5. Allow to dry completely
- 6. If tough marks remain, repeat "Heavy Cleaning" process using the same pad, or the other pads listed

Buff and Shine Floor

Once Floor is Cleaned and Completely Dry

Buff to shine with low speed "swing" buffer and a clean, dry red buffer pad

One Colgate Way, Canton, MA 02021 • (781) 821-8370 • Web Site: StatguardFlooring.com

© 2020 DESCO INDUSTRIES INC Employee Owned