



light source  
 work equipment  
 connected load  
 power consumption  
 luminous flux  
 luminous efficiency  
 light distribution  
 beam angle  
 color temperature  
 color temperature  
 color rendering index (CRI)  
 chromaticity tolerance LED  
 glare control  
 luminance (L65)  
 unified glare rating (4H 8H)  
 system of protection  
 class of protection  
 technology  
 operation  
 housing  
 cover  
 weight (net)  
 mains lead  
 fastening  
 dimension  
 minimum ambient temperature  
 maximum ambient temperature  
 special features

LED  
 without  
 24 V, DC  
 approx. 56 W  
 approx. 7,600 lm  
 approx. 135 lm/W  
 direct; symmetric  
 92°  
 cold white  
 approx. 5,000 K  
 CRI ≥ 80; R9 ≥ 10  
 < 3 SDCM  
 screen  
 ≤ 4,200 cd/m<sup>2</sup>  
 ≤ 22  
 IP 67  
 III  
 multi-stage switchable  
 external  
 aluminum; anodized; aluminum  
 colored anodized  
 borosilicate  
 env. 4.9 kg (10.8 lbs)  
 built-in plug; M12-A-5  
 screws  
 A=752.5 mm (29.63")  
 C=732.5 mm (28.84")  
 0 °C (32 °F)  
 50 °C (122 °F)  
 ADVANCED package

light distribution

